

## Lifting stati. Aqualift F XL 300l Duo, SPF 3000-S1, Backflow preventer



### Article information

Item no.: 11112  
 GTIN: 4026092057797  
 Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

#### Variant

Type of system: duo pump  
 Backflow preventer: integrated  
 Pressure pipe connection: vertical

#### General characteristics

Colour: black  
 Standard: EN 12050-1  
 Type of wastewater: with sewage  
 Installation situation: free-standing installation  
 System type: Duo

#### Dimensions

Net weight: 186,57 kg  
 Gross weight: 206,57 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Tank/drain body

Tank volume: 300 l

#### Pumping device

Pump:	SPF 3000
Number of pumps:	2
Length of mains cable for pump:	5 m
Operating mode:	S1
Impeller type:	Multi-vane impeller
Free passage:	40 mm
Control	
Control unit:	Comfort
Level measurement instrument:	Immersion pipe
Type of level measurement:	pneumatic
Mains frequency:	50 Hz
Operating voltage:	400 V