


## Submersible pump Aquadive GTF1000 without float switch, 10m



### Article information

Item no.: 28760  
GTIN: 4026092044520  
Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation:

GTF 1000

Variant

Rim width:

without float switch

General characteristics

Standard:

EN 12050-2

Type of wastewater:

without sewage

Dimensions

Net weight:

11,05 kg

Gross weight:

11,38 kg

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Wastewater contents

Pressure pipe connection:

R 1 ¼ "

Pumping device

Pump control:

GTF 1000

Connection type:

coded plug

Rated current:	5,6 A
Length of mains cable for pump:	10 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class control unit:	IP 68 (3m)
DSC:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug
Rated current:	5,6 A