



## Practicus floor/roof drain DN 70, vert, Waterpr layer, Des grating



### Article information

Item no.: 45270.53  
 GTIN: 4026092033845  
 Price group: 10

### Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

### Description

The Practicus floor drain is used for point drainage and is equipped with a connection flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Variant

System:

Waterproofing layer on the upper section:

Waterproofing layer on the drain body:

Sealing water height:

Discharge rate (l/s) with 20 mm backwater:

125

Enclosed sealing collar to be glued (bd) according to DIN 18534

Connection flange

50 mm

2,1

General characteristics

Standard:

Nominal size (DN):

Outer diameter (OD):

Inlet max. scoring (DN):

EN 1253-1

70

75 mm

Z-19.53-2414,Z-19.17-1719

**Dimensions**

|                      |                                     |
|----------------------|-------------------------------------|
| Vertical adjustment: | 10 - 23 mm                          |
| Net weight:          | 2,03 kg                             |
| Gross weight:        | 2,32 kg                             |
| Vertical adjustment: | vertically adjustable upper section |
| Length:              | 135 mm                              |
| Width:               | 135 mm                              |
| Packaging dimension: | length                              |
| Packaging dimension: | width                               |
| Packaging dimension: | height                              |

**Tank/drain body**

|                         |          |
|-------------------------|----------|
| Number of outlets:      | 1        |
| Material of drain body: | PP       |
| System:                 | vertical |

**Coverage features**

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| Type of cover:          | Design cover                                        |
| Cover material:         | Stainless steel 14301                               |
| Colour of cover:        | silver                                              |
| Width of cover:         | 120 mm                                              |
| Length of cover:        | 120 mm                                              |
| Surface:                | ground                                              |
| Frame material:         | Stainless steel 14301                               |
| Cover locking:          | Lock & Lift                                         |
| Load class:             | L 15 (EN 1253-1)                                    |
| Grating colour:         | Kessel                                              |
| Slip resistance class:  | R9 according to DIN 51130; C according to DIN 51097 |
| Rim length:             | 132 mm                                              |
| Rim material:           | 132 mm                                              |
| Upper section:          | adjustable in three dimensions                      |
| Shape of upper section: | square                                              |
| Upper section material: | ABS                                                 |
| Odour trap:             | included                                            |