

Shower channel Linearis Compact L: 950 mm, DN 50, WaD, 304 SST cov., K 3



Article information

Item no.: 45600.65M GTIN: 4026092078938

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant

System: 125 Seepage opening: prepared

Waterproofing layer on the upper section: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height:

Discharge rate (l/s) with 10 mm backwater:

0,6

Discharge rate (l/s) with 20 mm backwater:

0,7

Discharge rate (l/s) without backwater:

0,5 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
ATEX: no
Odour trap: included

Dimensions

Net weight:2,27 kgGross weight:3,06 kgOuter dimension, length:1015 mmInstallation depth:80 - 140 mmWidth:191 mmHeight:80 mm



Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Locking: placed

Load class: K 3 (EN 1253-1)
Grating design: optionally tileable

Rim width: 66 mm
Rim length: 950 mm
Max. flooring height: 15 mm
Upper section material: ABS