


## The Ultraflat 79 floor drain DN 50, Des grating





## **Article information**

Item no.: 44700.62 GTIN: 4026092080924 Price group: 10

## **Advantages**

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

## Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant System: SonicControl: Sealing water height:	125 optional 50 mm
General characteristics Standard: Nominal size (DN): Outer diameter (OD):	EN 1253-1 50 50 mm
Dimensions Vertical adjustment: Net weight: Gross weight: Vertical adjustment: Length: Width: Height: Packaging dimension: Packaging dimension:	88 - 139 mm 0,85 kg 1,01 kg vertically adjustable upper section 227 mm 163 mm 79 mm length width height



Tank/drain body Number of outlets: Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Height of cover: Length of cover: Surface: Frame material: Cover locking: Load class: Grating colour: Slip resistance class:

Rim length: Rim material: Shape of upper section: Upper section material: Odour trap: 1 ABS lateral

Design cover Stainless steel 14301 silver 120 mm 16 mm 120 mm ground Stainless steel 14301 unlocked L 15 (EN 1253-1) Kessel R9 according to DIN 51130; C according to DIN 51097 132 mm 132 mm square ABS included