


Scada wall drain w/cov, SST, 17 mm, fixed w/prf membrn



Article information

Item no.: 48000.04M
 GTIN: 4026092079140
 Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant	
Lighting:	without
Waterproofing layer on the drain body:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water supply:	W3-I
Sealing water height:	22 mm
Discharge rate (l/s) with 20 mm backwater:	0,5
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	58 mm
Dimensions	
Net weight:	2,29 kg
Gross weight:	2,45 kg
Length:	362 mm
Width:	195 mm
Height:	353 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Coverage features	
Type of cover:	Scada drain cover
Cover material:	Stainless steel 14301

Colour of cover:	silver
Height of cover:	67 mm
Length of cover:	312 mm
Min. flooring height:	22 mm
Frame material:	ABS
Cover locking:	inserted
Grating colour:	Standard 67
Max. flooring height:	26 mm
Shape of upper section:	square
Upper section material:	ABS
Odour trap:	included